5

10

15

20

## What is claimed is:

- 1. An optical fiber whose chromatic dispersion is -20 ps·nm<sup>-1</sup>·km<sup>-1</sup> or more but -3 ps·nm<sup>-1</sup>·km<sup>-1</sup> or less at all of the wavelengths in the range of 1300 nm to 1600 nm.
- 2. An optical fiber whose chromatic dispersion is -12 ps · nm · 1 · km · 1 or more but -4 ps · nm · 1 · km · 1 or less at all of the wavelengths in the range of 1300 nm to 1600 nm.
  - 3. An optical fiber whose chromatic dispersion is -20 ps nm · 1 km · 1 or more but -3 ps nm · 1 km · 1 or less at all of the wavelengths in the range of 1250 nm to 1650 nm.
  - 4. An optical fiber whose chromatic dispersion is -16 ps nm to 1650 nm.
  - 5. An optical fiber according to Claim 1, wherein the effective area at an wavelength of 1550 nm is  $40\,\mu\,\rm m^2$  or more.
  - 6. An optical fiber according to Claim 1, wherein the loss increase due to OH group at a wavelength of 1380 nm is 0.1 dB·km<sup>-1</sup> or less.
  - 7. An optical fiber according to Claim 1, wherein said optical fiber is provided with (1) a central core region including the center of optical axis and having a first refractive index, (2) a second core region enclosing the central core region and having a second refractive index which is smaller than the first refractive index, (3) a third core region enclosing the second core region and

5

10

15

20

having a third refractive index which is greater than the second refractive index, and (4) a clad region enclosing the third core region and having a fourth refractive index which is smaller than the third refractive index.

- 8. An optical fiber according to Claim 7, wherein said clad region includes an inner clad region having a refractive index smaller than said third refractive index and an outer clad region having a refractive index greater than the refractive index of the inner clad region.
- 9. An optical fiber according to Claim 7, wherein the relative refractive index difference of said central core region is 0.4% or more but 0.7% or less with respect to the refractive index of the outermost layer of said clad region.
  - 10. An optical transmission system comprising:
- a transmitting station to send out light signals having wavelengths in the range of 1300 nm to 1600 nm after multiplexing the same;

an optical fiber according to Claim 1 to transmit said light signals; and a receiving station to receive said light signals and demultiplex the same into their respective wavelengths.

- 11. An optical transmission system comprising:
- a transmitting station to send out light signals having wavelengths in the range of 1250 nm to 1650 nm after multiplexing the same;
- an optical fiber according to Claim 3 to transmit said light signals; and a receiving station to receive said light signals and demultiplex the same into their respective wavelengths.